



Maxtron® THF+

Full-Synthetic Tractor Hydraulic Fluid

General Description

Maxtron® THF+ is a full-synthetic multifunctional fluid formulated specifically for tractors which use a centralized system to lubricate the transmission, differential, wet brakes, power steering and hydraulic components.

Maxtron THF+ is formulated with premium synthetic base oils to provide excellent cold flow characteristics while maintaining high temperature viscosity stability. An exceptional additive package is used to provide anti-wear properties, which enables heavy differential gear loads and resistance to oxidation stress from high temperatures. Maxtron THF+ has a special balance of frictional properties which provides a smooth operation and also prevents wet brake chatter.

The fluid is designed to provide superior transmission and hydraulic operations at all temperatures with an emphasis on sub-zero weather conditions. Additionally, Maxtron THF+ is superior at keeping the internal parts clean and prolonging the life of seal materials.

Excellent performance in these applications:

- Tractors that have a common sump for transmissions, hydraulics, differentials and wet brakes
- All-season equipment operations
- Wear and oxidation control
- Prevention of wet brake chatter
- Viscosity retention

Features and Benefits

- **Viscosity Stability:** The full-synthetic base oil formulation offers a high viscosity index as well as excellent shear stability and superior low temperature performance.
- **Pumping Efficiency:** Retains viscosity at high temperatures and minimizes viscosity shear loss, which increases hydraulic power output at all operating temperatures.
- **Low Temperature Performance:** Excellent fluidity and superb hydraulic system operation at sub-zero temperatures.
- **Chatter Free:** Outstanding frictional properties that reduce noise and damage caused by wet brake chatter.
- **Compatibility:** Prolongs life of oil seals and hydraulic hoses, which reduce downtime.
- **Wear Protection:** Protects gears, pumps and other parts from wear due to heavy loads, therefore extending equipment life.
- **System Cleanliness:** Keeps all system parts clean and varnish free for smooth operation.
- **Oil Durability:** Superior oxidation control reduces oil degradation from high operating temperatures providing longer oil life.
- **Expect superior performance in:** Agriculture, off-highway and construction equipment calling for J20-C, THF or UTTO Fluid.

Maxtron[®] THF+

Full-Synthetic Tractor Hydraulic Fluid

CHS Lubricants recommends that Cenex[®] Maxtron[®] THF+ is suitable for use in the following applications:

AGCO: Power Fluid 821, 821 XL **Allison:** C-2 (Obsolete), C-3 (Obsolete), and C-4 **Case-IH:** Akcela, Hy-Tran[®], Hy-Tran[®] Plus, Hy-Tran[®] Ultra, MAT-3540, MAT-3505, MS-1210, 1209, 1207, 1206, JIC144/145, Power PRF **Caterpillar:** MTO **Deutz/Allis:** Power Fluid 821 **Ford New Holland:** Ambra Multi-G 134, Mastertran Ultraction (MAT-3540), M2Ci-34 A,B,C,D, M2C-41B, M2C-53 A,B, M2C-86B, MAT-3525 **Hesston/Fiat:** Olio fiat Tutela Multi-F

John Deere: Hy-Gard J20 C/A, JD 303, J14 C/B **Kubota:** Kubata UDT Fluid, Transdraulic Fluid, Super UDT **Massey Ferguson:** M-1145, 1143, Permatran III, MF-1127A/B, MF1129A, McCormick HTX **Steiger:** Hydraulic/Transmission Fluid 17001 **Versatile:** HyGear Fluid, Specification 23, Volvo VME WB-101, VCE 1273.03 **White/Oliver/MM:** AG ONE, Universal Fluid, Type 55, Q-1826 HTF

Typical Properties

Property	Typical Result
SAE Grade (approximate)	5W-30
API Gravity/Density lbs/gal	33.5/7.14
Viscosity, cSt @ 40°C (SSU)	54.5 (253)
Viscosity, cSt @ 100°C (SSU)-	10.5 (61)
Viscosity Index	184
Pour Point, °F (°C)	-54 (-48)
Brookfield Viscosity, cP @ -20 °C	2300
Brookfield Viscosity, cP @ -40 °C	29000
Foam Test ASTM D892	Pass
DKA Oxidation Test	Pass
Seal Compatibility	Pass
OEM Shear Stability	Pass
API Gear Performance	GL-4
Color	Blue

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.

Health & Safety

A complete safety data sheet is available by calling 1-651-355-8438 or visit cenex.com/sds-library.