



4x4 / ELECTRIC



Shown with optional accessories.



HOOD COLORS	
FACTORY-INSTALLED PACKAGES	Untamed Trail Cruiser
TIRE OPTIONS	Max Terrain (Standard) / Trail Rider / Cruiser / Turf / Gladiator
BED OPTIONS	Poly Bed, Large Steel Bed, Flip Seat / Steel Bed
MOTOR	AC motor, 48V Lithium-Ion Battery, 600 amp Controller
SPEED / RANGE	30 mph (24 mph with Rear Flip Seat) / Up to 50 Miles
ELECTRONIC POWER STEERING	Included
BED CAPACITY	400 lbs / 600 lbs (with HD Shocks)
TOW	1,500 lbs



AMERICAN MADE UTVs



4x4 / ELECTRIC

THE BEST COMBINATION OF DURATION AND COVERAGE IN THE INDUSTRY

We build UTVs at American LandMaster with the intention of our customers never needing to use a warranty, but we know things can happen. The **Easy Life Warranty** from American LandMaster is a 12-month bumper-to-bumper limited warranty. Does limited sound confusing? It isn't. **As long as you care for your machine like you should, don't wreck it, or crush it, we're going to cover it.** Except for tires, brake pads, batteries, damage, neglect. That's the limit. **Visit Landmaster.com to learn more.**

POWER	AC motor, powered by a 48V DC Lithium-Ion Battery up to 8K Watts with 600 amp controller
SEATING CAPACITY	4 Person
SPEED	30MPH (24MPH with Rear Flip Seat)
FUEL CONSUMPTION	N/A
RANGE	Up to 50 miles (160 ah battery)*
STARTING	Keyed on/off
BATTERY	48V 160AH Lithium-Ion
SPARK PLUG	N/A
FUEL CAPACITY	N/A
ALTERNATOR	Converter / 30 amps
TRANSMISSION	Direct drive
TRANSAXLE	Model 24 Schafer
DIFFERENTIAL	Cable Activated Locking
DRIVE	4wd (Switch engaged on demand, 4 wheel drive)
FRONT SUSPENSION	Double A-arms, adjustable coil over shock with up to 8" travel
REAR SUSPENSION	Independent trailing arm, with radius rod, adjustable camber & tow control, dual-rate coil over shock with up to 8" of travel
BRAKE SYSTEM	4 wheel disc, hydraulic brake
TIRES	25" Standard Max-Terrain HD DOT / Radial 8 Ply Tires on 12" Steel Wheels
DIMENSIONS	127" L x 58" W x 76" H (with poly bed)**
WHEEL BASE	105"
TURNING RADIUS	14'
GVWR	2,530 lbs.
CURB WEIGHT	1,530 lbs. with 160 AH battery
BED MATERIALS	Structural foam "Poly Bed" with stake pockets
BED DIMENSIONS	35.25" L x 41.5" W x 11" D
BED CAPACITY	Poly - 9 cu.ft. / Steel - 11 cu.ft. / L-ROSS - 400 lbs. / HD L-ROSS - 600 lbs.
TOWING CAPACITY	1,500 lbs.
TOTAL PAYLOAD	1,000 lbs.
WARRANTY	1 year motor / all other 1 year limited, 5 year prorated Lithium battery
ADDITIONAL FEATURES	On-board charger, 3pt lap/ shoulder belts for driver & passenger, 12V/18W LED headlights, 2" rear and front receiver hitch, welded steel frame, Single 12V auxiliary outlet for accessories, polyurethane powder paint. Complete weather-sealed wiring connections. Wide selection of additional accessories available along with three bed options. In-dash, hour meter standard. LED true state of charge meter for the 48 volt system is standard. Low charge audible warning. Battery shut down switch. Electric accelerator pedal.

* Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances.
 **Overall vehicle dimensions may vary with the addition of optional accessories