



# Aerosol Rub-O-Matic

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Issue date: 6/6/2023 Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : Aerosol Rub-O-Matic  
Product code : 704A

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Rubber  
Cleaner  
Restrictions on use : No additional information available

#### 1.3. Supplier

##### Manufacturer

Tech International  
200 East Coshocton Street  
Johnstown, OH 43031, USA  
1-740-967-9015  
www.tech-international.com

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC  
Within USA and Canada: 1-800-424-9300  
Outside USA and Canada: +1-703-527-3887  
Local: +1 703-741-5970

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable aerosol Category 1	H222	Extremely flammable aerosol
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Hazardous to the aquatic environment – Acute Hazard Category 1	H400	Very toxic to aquatic life
Hazardous to the aquatic environment – Chronic Hazard Category 1	H410	Very toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger  
Hazard statements (GHS US) : H222 - Extremely flammable aerosol  
H315 - Causes skin irritation  
H336 - May cause drowsiness or dizziness  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects

# Aerosol Rub-O-Matic

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Pressurized container: Do not pierce or burn, even after use.  
P261 - Avoid breathing spray.  
P264 - Wash hands thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection.  
P302+P352 - If on skin: Wash with plenty of soap and water.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P312 - Call a POISON CENTER, a doctor if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P391 - Collect spillage.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Comments : The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of § 1910.1200

Name	Product identifier	%	GHS US classification
Solvent naphtha (petroleum), light aliph.	CAS-No.: 64742-89-8	≥ 40 – < 60	Asp. Tox. 1, H304
Heptane	CAS-No.: 142-82-5	≥ 25 – < 40	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Propane	CAS-No.: 74-98-6	< 20	Flam. Gas 1, H220
Isobutane	CAS-No.: 75-28-5	< 20	Flam. Gas 1, H220

Full text of hazard classes and H-statements : see section 16

# Aerosol Rub-O-Matic

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Give oxygen or artificial respiration if necessary. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Wash skin thoroughly with mild soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Ingestion is not considered a potential route of exposure. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause drowsiness or dizziness. In high concentrations vapors cause anesthetic and narcotic effect.
Symptoms/effects after skin contact	: Causes skin irritation, Redness, Itching, Swelling.
Symptoms/effects after eye contact	: Lacrimation, Redness, itching, tears, Blurred vision.
Symptoms/effects after ingestion	: Ingestion is not considered a potential route of exposure.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry powder. Carbon dioxide. Water spray. Foam. Use extinguishing agent suitable for surrounding fire.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol. Heating will cause a rise in pressure with a risk of bursting. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: Contains gas under pressure; may explode if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released, Carbon dioxide, Carbon monoxide.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Evacuate the danger area, Eliminate all ignition sources if safe to do so. Move containers from fire area if it can be done without personal risk. Use water spray or fog for cooling exposed containers. Fight fire from safe distance and protected location. Use extinguishing media appropriate for surrounding fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing. Do not attempt to take action without suitable protective equipment.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: No flames, no sparks. Eliminate all sources of ignition. Use special care to avoid static electric charges. Avoid all contact with skin, eyes, or clothing.
------------------	---

##### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
----------------------	---

# Aerosol Rub-O-Matic

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures : Evacuate unnecessary personnel. Ventilate spillage area. Avoid breathing spray. Avoid contact with skin and eyes. No action shall be taken without appropriate training or involving any personal risk. No flames, no sparks. Eliminate all sources of ignition.

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment.  
Emergency procedures : Evacuate unnecessary personnel. Use non-sparking tools. Ventilate area. No naked flames, sparks, and do not smoke.

## 6.2. Environmental precautions

Avoid release to the environment. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters.

## 6.3. Methods and material for containment and cleaning up

For containment : Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Remove ignition sources.  
Methods for cleaning up : Move containers from spill area. Leave the product to evaporate. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Clean contaminated surfaces with an excess of water. Prevent entry to sewers and public waters. Use non-sparking tools. Keep in suitable, closed containers for disposal.  
Other information : Dispose of via an authorised person/ licensed waste disposal contractor or by other suitable waste treatment techniques. Dispose of materials or solid residues at an authorized site.

## 6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Ensure good ventilation of the work station. Provide local exhaust or general room ventilation. Avoid breathing spray. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Eliminate all ignition sources if safe to do so. Take precautionary measures against static discharge. Use explosion-proof equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.  
Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Strong oxidizers. Store in a dry place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from food, drink and animal feed. Keep container tightly closed. Store in accordance with local, regional, national or international regulation. Do not store in unlabelled containers. Do not expose to temperatures exceeding 50 °C/ 122 °F.

# Aerosol Rub-O-Matic

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Heptane (142-82-5)	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Heptane, isomers (n-Heptane)
ACGIH OEL TWA	400 ppm
ACGIH OEL STEL	500 ppm
Remark (ACGIH)	TLV® Basis: CNS impair; URT irr
Regulatory reference	ACGIH 2023
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Heptane (n-Heptane)
OSHA PEL TWA	2000 mg/m <sup>3</sup>
	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Propane (74-98-6)	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Propane
Remark (ACGIH)	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2023
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Propane
OSHA PEL TWA	1800 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Isobutane (75-28-5)	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Isobutane
ACGIH OEL STEL	1000 ppm (EX - Explosion hazard)
Remark (ACGIH)	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2023
<b>Monitoring methods</b>	
Monitoring methods	Refer to all applicable national, international and local regulations or provisions.

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure exposure is below occupational exposure limits (where available). Handle in accordance with good industrial hygiene and safety procedures. Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

# Aerosol Rub-O-Matic

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental exposure controls : Avoid release to the environment. Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment. Personal protective equipment should be chosen according to the NIOSH standards and in discussion with the supplier of the protective equipment.

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer

#### Eye protection:

Chemical goggles or safety glasses

#### Skin and body protection:

Wear suitable protective clothing. Skin protection appropriate to the conditions of use should be provided

#### Respiratory protection:

An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol.
Color	: clear
Odor	: strong Solvent
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: -9 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.724
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

# Aerosol Rub-O-Matic

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

#### 10.2. Chemical stability

Stable under normal conditions of use.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Hazardous polymerization: Will not occur.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Protect from sunlight. Overheating. Extremely high or low temperatures. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Oxidising agents.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Solvent naphtha (petroleum), light aliph. (64742-89-8)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

#### Heptane (142-82-5)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Vapours)	> 29.29 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : May cause drowsiness or dizziness.

#### Heptane (142-82-5)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified  
Aspiration hazard : Not applicable  
Viscosity, kinematic : No data available

# Aerosol Rub-O-Matic

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after inhalation	: May cause drowsiness or dizziness. In high concentrations vapors cause anesthetic and narcotic effect.
Symptoms/effects after skin contact	: Causes skin irritation. Redness. Itching. Swelling.
Symptoms/effects after eye contact	: Lacrimation. Redness, itching, tears. Blurred vision.
Symptoms/effects after ingestion	: Ingestion is not considered a potential route of exposure.
Other information	: No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.

#### Solvent naphtha (petroleum), light aliph. (64742-89-8)

LC50 - Fish [1]	10 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	2.6 mg/l 21d, Daphnia magna

#### Heptane (142-82-5)

LC50 - Fish [1]	4 mg/l (Carassius auratus)
EC50 - Crustacea [1]	1.15 mg/l

### 12.2. Persistence and degradability

#### Aerosol Rub-O-Matic

Persistence and degradability : Biodegradability in water: no data available.

### 12.3. Bioaccumulative potential

#### Aerosol Rub-O-Matic

Bioaccumulative potential : No data available concerning bioaccumulation.

#### Heptane (142-82-5)

Bioconcentration factor (BCF REACH) : 552

### 12.4. Mobility in soil

#### Aerosol Rub-O-Matic

Ecology - soil : No additional information available.

#### Heptane (142-82-5)

Organic Carbon Normalized Adsorption Coefficient (Log Koc) : 2.38

### 12.5. Other adverse effects

Other adverse effects : No other effects known.  
Effect on global warming : No known effects from this product.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.



# Aerosol Rub-O-Matic

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.
Ecological information	: Avoid release to the environment.

### SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

#### 14.1. UN number

DOT NA No	: UN1950
UN-No. (TDG)	: UN1950
UN-No. (IMDG)	: 1950
UN-No. (IATA)	: 1950


#### 14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Aerosols
Proper Shipping Name (TDG)	: AEROSOLS
Proper Shipping Name (IMDG)	: AEROSOLS
Proper Shipping Name (IATA)	: Aerosols, flammable

#### 14.3. Transport hazard class(es)

##### DOT

Transport hazard class(es) (DOT)	: 2.1
Hazard labels (DOT)	: 2.1



##### TDG

Transport hazard class(es) (TDG)	: 2.1
Hazard labels (TDG)	: 2.1



##### IMDG

Transport hazard class(es) (IMDG)	: 2.1
Hazard labels (IMDG)	: 2.1



##### IATA

Transport hazard class(es) (IATA)	: 2.1
Hazard labels (IATA)	: 2.1



# Aerosol Rub-O-Matic

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.4. Packing group

Packing group (DOT)	: Not applicable
Packing group (TDG)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable

### 14.5. Environmental hazards

Dangerous for the environment	: Yes
Marine pollutant	: Yes



Other information	: No supplementary information available.
-------------------	---

### 14.6. Special precautions for user

#### DOT

UN-No.(DOT)	: UN1950
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### TDG

UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

#### IMDG

Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

# Aerosol Rub-O-Matic

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Stowage category (IMDG) : None  
Stowage and handling (IMDG) : SW1, SW22  
Segregation (IMDG) : SG69

### IATA

PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
Special provision (IATA) : A145, A167, A802  
ERG code (IATA) : 10L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

#### CANADA

#### Solvent naphtha (petroleum), light aliph. (64742-89-8)

Listed on the Canadian DSL (Domestic Substances List)

#### Heptane (142-82-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

#### Isobutane (75-28-5)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

#### Solvent naphtha (petroleum), light aliph. (64742-89-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Heptane (142-82-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

# Aerosol Rub-O-Matic

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Propane (74-98-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Isobutane (75-28-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Data sources : Supplier's safety documents.

Training advice : Training staff on good practice.

### Full text of H-phrases

H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.