



## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.28.2016

Page 1 of 12

Revision date: 08.11.2020

**Bead Sealer**

### SECTION 1: Identification

#### Product identifier

**Product name:** Bead Sealer  
**Product code:** 735, 735G, 735-5G, 735-55G  
**Additional information:** Rev. 6

#### Recommended use of the product and restriction on use

**Relevant identified uses:** Rubber adhesive  
**Uses advised against:** Not determined or not applicable.  
**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

**Manufacturer:**  
**North America**  
Tech International  
200 East Coshocton Street  
Johnstown, OH 43031  
1-740-967-9015  
www.tech-international.com

#### Emergency telephone number:

**United States**  
CHEMTREC  
Within USA and Canada: 1-800-424-9300  
Outside USA and Canada: +1-703-527-3887

### SECTION 2: Hazard(s) identification

#### GHS classification:

Flammable liquids, category 2  
Skin irritation, category 2  
Specific target organ toxicity - single exposure, category 3, central nervous system

#### Label elements

##### Hazard pictograms:



**Signal word:** Danger

#### Hazard statements:

H225 Highly flammable liquid and vapor  
H315 Causes skin irritation  
H336 May cause drowsiness or dizziness

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.28.2016

Page 2 of 12

Revision date: 08.11.2020

## Bead Sealer

### Precautionary statements:

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical/ventilating/light/equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P264 Wash skin thoroughly after handling
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P271 Use only outdoors or in a well-ventilated area
- P302+P352 IF ON SKIN: Wash with soap and water
- P303+P361+P353 IF ON SKIN (or hair): Immediately remove/take off all contaminated clothing. Rinse skin with water/shower
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P301+P310 IF SWALLOWED: Immediately call a poison center or doctor/physician
- P331 Do not induce vomiting
- P332+P313 If skin irritation occurs: Get medical advice/attention
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P321 Specific treatment (see supplemental first aid instructions on this label).
- P362 Take off contaminated clothing and wash before reuse
- P370+P378 In case of fire: Use agents recommended in section 5 for extinction
- P405 Store locked up
- P403+P233 Store in a well ventilated place. Keep container tightly closed
- P403+P235 Store in a well ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified: None

## SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	80-90
CAS number: 9003-31-0	Natural Rubber	9-15
CAS number: 142-82-5	Heptane	<4
CAS number: 1333-86-4	Carbon Black	1.5-3
CAS number: 68476-34-6	Diesel Fuel No. 2	<0.1

### Additional Information:

Carbon black is classified as a carcinogen only in its respirable form. Since the carbon black in this product is not respirable, the product itself is not classified as a carcinogen in the form presented. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.28.2016

Page 3 of 12

Revision date: 08.11.2020

## Bead Sealer

### SECTION 4: First aid measures

#### Description of first aid measures

##### General notes:

Show this Safety Data Sheet to the doctor in attendance

##### After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention

##### After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention

##### After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention

##### After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention

#### Most important symptoms and effects, both acute and delayed

##### Acute symptoms and effects:

Product is highly flammable. Exposure to sources of ignition may cause physical injury  
Skin contact may result in redness, pain, burning and inflammation  
Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness

##### Delayed symptoms and effects:

Overexposure via inhalation requires urgent medical treatment  
Effects are dependent on exposure (dose, concentration, contact time)

#### Immediate medical attention and special treatment

##### Specific treatment:

Not determined or not applicable.

##### Notes for the doctor:

Treat symptomatically

### SECTION 5: Firefighting measures

#### Extinguishing media

##### Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

##### Unsuitable extinguishing media:

Do not use a water stream as an extinguisher

#### Specific hazards during fire-fighting:

Highly flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.28.2016

Page 4 of 12

Revision date: 08.11.2020

## Bead Sealer

They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation

### Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode

### Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling

### Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided

### Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13)

### Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13

## SECTION 7: Handling and storage

### Precautions for safe handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

### Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.28.2016

Page 5 of 12

Revision date: 08.11.2020

## Bead Sealer

ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

#### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
United States (OSHA)	Heptane	142-82-5	OSHA PEL TWA: 500 ppm
	Heptane	142-82-5	OSHA PEL TWA 2,000 mg/m <sup>3</sup>
ACGIH	Heptane	142-82-5	ACGIH TLV TWA: 400 ppm
	Diesel Fuel No. 2	68476-34-6	ACGIH TLV TWA: 100.0 mg/m <sup>3</sup> (Vapor and aerosol as total hydrocarbons)
	Heptane	142-82-5	15-minute Short term exposure limit: 1000 mg/m <sup>3</sup>
	Carbon Black	1333-86-4	TLV-TWA 3.0 mg/m <sup>3</sup>
NIOSH	Carbon Black	1333-86-4	NIOSH REL TWA 3.5 mg/m <sup>3</sup> Ca
	Heptane	142-82-5	NIOSH TWA: 350 mg/m <sup>3</sup> (85 ppm)
	Heptane	142-82-5	10-hour REL: 350 mg/m <sup>3</sup> (85 ppm)
	Heptane	142-82-5	Ceiling limit: 1800 mg/m <sup>3</sup> (440 ppm)
	Carbon Black	1333-86-4	NIOSH REL TWA 0.1 mg PAHs/m <sup>3</sup> [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)]

#### Biological limit values:

No biological exposure limits noted for the ingredient(s).

#### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

#### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Use explosion-proof ventilation equipment.

#### Personal protection equipment

##### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

##### Skin and body protection:

Select glove material impermeable and resistant to the substance. For continuous contact, we recommend nitrile gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Always seek advice from glove suppliers.

##### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.28.2016

Page 6 of 12

Revision date: 08.11.2020

## Bead Sealer

(where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Comply with the OSHA respirator regulations found in 29 CFR 1910.134.

### General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Black Viscous Liquid
Odor	Strong Solvent
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	190°F (88°C)
Flash point (closed cup)	15°F (-9°C)
Evaporation rate	>1 (n-BuAC=1)
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	6.7% (V)
Lower flammability/explosive limit	1.2% (V)
Vapor pressure	119 mmHg at 20°C (68°F)
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	0.73 g/cm <sup>3</sup> (6.22 lbs./gal) at 20°C (68°F)
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	15000
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

### Other information

VOC	613 g/L
-----	---------

## SECTION 10: Stability and reactivity

### Reactivity:

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.28.2016

Page 7 of 12

Revision date: 08.11.2020

## Bead Sealer

Does not react under normal conditions of use and storage.

### Chemical stability:

Stable under normal conditions of use and storage.

### Possibility of hazardous reactions:

None under normal conditions of use and storage.

### Conditions to avoid:

Excess heat, ignition source or flames.

### Incompatible materials:

None known.

### Hazardous decomposition products:

None known.

## SECTION 11: Toxicological information

### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Route	Result
Heptane	inhalation	LC50 Rat: > 29.29 mg/L (4 hr)
	oral	LD50 Rat: > 5000 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	oral	LD50 Rat: > 5000 mg/kg
	dermal	LD50 Rabbit: > 2000 mg/kg
	inhalation	LC50 Rat: > 4.42 mg/L (4 hr, vapor)

### Skin corrosion/irritation

#### Assessment:

Causes skin irritation

#### Product data:

No data available.

#### Substance data:

Name	Result
Heptane	Causes skin irritation.
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Causes skin irritation.

### Serious eye damage/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Respiratory or skin sensitization

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.28.2016

Page 8 of 12

Revision date: 08.11.2020

## Bead Sealer

### Carcinogenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Species	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not applicable	The carcinogenic classification applies to naphtha streams containing >0.1% Benzene.
Carbon Black	Not applicable	The IARC carcinogenic classification and California Proposition 65 Warning only apply to airborne, unbound particles of respirable size of Carbon Black.

### International Agency for Research on Cancer (IARC):

Name	Classification
Carbon Black	Group 2B - Possibly carcinogenic to humans
Natural Rubber	Group 3 - Not classifiable as to its carcinogenicity to humans
Diesel Fuel No. 2	Group 2B - Possibly carcinogenic to humans

**National Toxicology Program (NTP):** None of the ingredients are listed.

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The mutagenic classification applies to naphtha streams containing >0.1% Benzene.

### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The classification as a reproductive toxicant only applies when the naphtha stream contains >3% toluene and/or n-hexane.

### Specific target organ toxicity (single exposure)

**Assessment:**

May cause drowsiness or dizziness

**Product data:**

No data available.

**Substance data:**



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.28.2016

Page 9 of 12

Revision date: 08.11.2020

## Bead Sealer

Name	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	May cause drowsiness or dizziness.
Heptane	May cause drowsiness or dizziness.

### Specific target organ toxicity (repeated exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Heptane	May be fatal if swallowed and enters airways.
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	May be fatal if swallowed and enters airways.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

Refer to Section 4 of this SDS.

**Other information:**

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:**

Toxic to aquatic life

**Product data:** No data available.

**Substance data:**

Name	Result
Heptane	LC50 - Carassius auratus (goldfish) - 4 mg/l - 24.0 h
	EC50 - Daphnia magna - 82.5 mg/L - 96 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	ErC50 Selenastrum capricornutum: 3.1 mg/L (72 hr)
	EC50 Daphnia magna: 4.5 mg/L (48 hr)

### Chronic (long-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.28.2016

Page 10 of 12

Revision date: 08.11.2020

## Bead Sealer

Name	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	EC50 Daphnia magna: 10 mg/L (10 days)

### Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Heptane	Readily biodegradable in water.
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance (UVCB).

### Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Heptane	Calculated BCF: 552 (Not expected to bioaccumulate).
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance (UVCB).

### Mobility in soil

Product data: No data available.

Substance data:

Name	Result
Heptane	Moderately Mobile (log Koc: 2.38)

Other adverse effects: No data available.



## SECTION 13: Disposal considerations

### Disposal methods:

Dispose in accordance with all applicable regulations. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

## SECTION 14: Transport information

### United States Transportation of dangerous goods (49 CFR DOT)

UN number	UN1133
UN proper shipping name	Adhesives
UN transport hazard class(es)	3  
Packing group	II
Environmental hazards	Marine Pollutant (Heptane and Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)
Special precautions for user	None

### International Maritime Dangerous Goods (IMDG)

# Safety Data Sheet



According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.28.2016



Page 11 of 12

Revision date: 08.11.2020

**Bead Sealer**

UN number	UN1133	
UN proper shipping name	Adhesives	
UN transport hazard class(es)	3	 
Packing group	II	
Environmental hazards	Marine Pollutant (Heptane and Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)	
Special precautions for user	None	

**International Air Transport Association Dangerous Goods Regulations (IATA-DGR)**

UN number	UN1133	
UN proper shipping name	Adhesives	
UN transport hazard class(es)	3	 
Packing group	II	
Environmental hazards	Marine Pollutant (Heptane and Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)	
Special precautions for user	None	

<b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	
Bulk Name	None
Ship type	None
Pollution category	None

**SECTION 15: Regulatory information**

**United States regulations**

**Inventory listing (TSCA):** All ingredients are listed or exempt.

**Significant New Use Rule (TSCA Section 5):** None of the ingredients are listed.

**Export notification under TSCA Section 12(b):** None of the ingredients are listed.

**SARA Section 302 extremely hazardous substances:** None of the ingredients are listed.

**SARA Section 313 toxic chemicals:** None of the ingredients are listed.

**CERCLA:** None of the ingredients are listed.

**RCRA:** None of the ingredients are listed.

**Section 112(r) of the Clean Air Act (CAA):** None of the ingredients are listed.

**Massachusetts Right to Know:**

9003-31-0	Natural Rubber	Not Listed
68476-34-6	Diesel Fuel No. 2	Not Listed
1333-86-4	Carbon Black	Listed
142-82-5	Heptane	Listed

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.28.2016

Page 12 of 12

Revision date: 08.11.2020

## Bead Sealer

64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Listed
------------	--	--------

### New Jersey Right to Know:

9003-31-0	Natural Rubber	Not Listed
68476-34-6	Diesel Fuel No. 2	Not Listed
1333-86-4	Carbon Black	Listed
142-82-5	Heptane	Listed
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Listed

### New York Right to Know:

9003-31-0	Natural Rubber	Not Listed
68476-34-6	Diesel Fuel No. 2	Not Listed
1333-86-4	Carbon Black	Not Listed
142-82-5	Heptane	Listed
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not Listed

### Pennsylvania Right to Know:

9003-31-0	Natural Rubber	Not Listed
68476-34-6	Diesel Fuel No. 2	Listed
1333-86-4	Carbon Black	Listed
142-82-5	Heptane	Listed
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Listed

California Proposition 65: None of the ingredients are listed.

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

### Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 2-3-0

**HMIS:** 2-3-0

Initial preparation date: 06.28.2016

Revision date: 08.11.2020

End of Safety Data Sheet